

LW 5115-BI

Discontinued products

BASS:	1 x 15" speaker with 2,5" voice coil
MID:	1 x 8" speaker with 1,46" voice coil
TREBLE:	1 x 1" driver with 1" PM4 voice coil
HORN:	90° x 40° for mid-high range LW 5115 HFD-HFM with pan/tilt adjustment
POWER:	5115BI 300+160W AES/600+320W Prg. Nominal impedance 8+8 ohm.
SENSITIVITY:	LF unit: Sens 96,5dB/1W/1m. Half space SPL 121,9dB MF/HF unit: Sens 94dB/1W/1m. Free field SPL 116,3dB
FREQUENCY RESPONSE:	(-10dB) 32,8 to 20.000 Hz.
SIZE:	158 x 66 x 27 cm.
WEIGHT:	60 Kg.



Dedicated to horn loaded traditional technology lovers, our 5000 Series is still being manufactured.

Two versions can be chosen, for Passive mode or for Biamp. Including a pan/tilt aiming device for the mid-high horn. This 3 way system shallow profile (27cm (10" depth) cabinet screen system has an internal crossover/processor with SCD (Projection Screen Compensation Device) and is suitable for up to 300 seat cinemas.

Despite its small size the quality is superb. And when working with either a set of two LW 6107 subwoofers or one 2x18" LW 6113, and our range of LW Amplifiers, it covers the complete frequency range for this very special kind of sound called Cinema Sound. All this can be achieved thanks to the professional European components used in the manufacturing.

As every LW Speakers model, the unit is painted with the strongest possible finishing: the polyurea.

To save labour costs, it is delivered pre-assembled in two cartons.

Presets for installation:

- X-over, 200 Hz
- Phase not inverted
- No delays

EQ for medium/treble unit:

- EQ1: 1.500Hz/Q1.8 -4dB
- EQ2: 2.700Hz/Q2 -4dB
- No EQ for bass unit