

LW 5117-BI

Discontinued products

BASS:	2 x 15" speaker with 2,5" voice coil
MID:	1 x 8" speakers with 1,46" voice coil
TREBLE:	1 x 1" driver with 1" PM4 voice coil
HORN:	90° x 40° for mid-high range LW 5115 HFD-HFM with pan/tilt adjustment
POWER:	160+600W AES, 320+1200W Prg. Nominal impedance 8+4 ohm.
SENSITIVITY:	LF unit: Sens 99,5dB/1W/1m. Half space SPL 128dB MF/HF unit: Sens 94dB/1W/1m. Free field SPL 116,3dB
FREQUENCY RESPONSE:	(-10dB) 38Hz-20.000 Hz. Use 400Hz. crossover.
SIZE:	175 x 66 x 47,6 cm.
WEIGHT:	Net 71 kg.



Dedicated to horn loaded traditional technology lovers, our 5000 Series is still being manufactured.

The LW 5117-BI is ready for Biamp operations (see presets below), and includes a pan/tilt aiming device for the mid-high horn. This 3 way system is suitable for up to 350 seat cinemas.

The quality is superb, and when working with one or two 2x18" LW 6113, and our range of LW Amplifiers, it covers the complete frequency range for this very special kind of sound called Cinema Sound. All this can be achieved thanks to the professional European components used in the manufacturing.

As every LW Speakers model, the unit is painted with the strongest possible finishing: the polyurea.

To save labour costs, it is delivered pre-assembled in two cartons.

Presets for installation:

- X-over, 200 Hz
- Phase not inverted
- No delays

EQ for medium/treble unit:

- EQ1: 1.500Hz/Q1.8 -4dB
- EQ2: 2.700Hz/Q2 -4dB
- No EQ for bass unit

