

LW 7501

Discontinued products

BASS:	1 x 10" speaker
MID:	
TREBLE:	1 x 1" driver with 1" voice coil
HORN:	100° x 60° constant directivity horn.
POWER:	250W AES/500W Prg. 8 ohm. Nominal Impedance 8 ohm.
SENSITIVITY:	95,5dB/1W/1m. Free field SPL 120dB - SPL 123dB with musical criteria
FREQUENCY RESPONSE:	(-10dB) 40Hz. to 18.000Hz.
SIZE:	46 x 46 x 25,5 (12,5) cm.
WEIGHT:	Net 8,0 kg.



The LW 7501 is the third system of our ABS Surrounds. These are very easy to install on walls or ceiling because of its extreme lightness. Can be installed by just one technician.

The system is delivered with a standard fixed support, but its also ready to work with our pan/tilt wall/ceiling support LW 7712 SUPPORT for immersive systems.

Despite the ABS cabinet the system is improved with an internal and special treatment to achieve a very low frequency of resonance. This enables the technician to EQ in a wider range of frequencies.

Because of the improved quality of the sound at cinemas, it is very common nowadays to fit the surround channel with subwoofers, not only for Immersive Systems, but also for good 5.1 and 7.1 installations. For this reason, we are offering our LW 7513 SUB or our LW 7517 V2 SUB to work with our LW 7501.

Dark grey colour is the standard delivery, but the grill could be painted any color following the customer needs.

