

## LW 8001-BI V2

## Screen systems

BASS:	2 x 15" speaker with 2,5" voice coil
MID:	2 x 6" speaker with 1,46" voice coil
TREBLE:	2 x 1" driver with 1" voice coil
HORN:	2 x Isophasic ABS horns, 140° x 12° each. With pan/tilt adjustment.
POWER:	Bass system, 500W AES/1000W Prg. 4 ohm. Medium/treble system 310W AES/620W Prg. 4 ohm.
SENSITIVITY:	LF Unit: 100dB/1W/1m. - SPL 127dB - SPL 130dB with musical criteria MHF unit: 95dB/1W/1m. - SPL 120dB - SPL 123dB with musical criteria
FREQUENCY RESPONSE:	37/22.000 Hz. For bi-amp cut off frequency use a single crossover working at 150Hz. We recommend using our LW 8080 processor, which is delivered with all necessary presets.
SIZE:	144,7 x 66 x 60,4 cm.



A screen system including LAT2014 (Line Array Technology), which combines professional compression drivers with true isophasic horns to achieve an extreme -3dB coverage throughout the whole audience area. 2 x 15" bass section plus a middle-treble section with Line Array Technology and 2 x 6" medium drivers plus 2 x 1" compression drivers + 2 x isophasic horns. We strongly recommend this model as the natural replacement to our discontinued products LW 2203-BI and LW 5107-BI.

